



(RENOVATION RIBBED ABRASIVE BARS)

Distributed by:

**Canadian Master Distributor**

✉ [sales@cityscapesupply.com](mailto:sales@cityscapesupply.com)

🌐 [cityscapesupply.com](http://cityscapesupply.com)

☎ 647 498 3417



**SPECIFICATIONS:**

- ① **BASE:** EXTRUDED ALUMINUM ALLOY 6063 T-6
- ② **ABRASIVE:** ALUMINUM OXIDE SILICON CARBIDE GRANULES IN A UV PROTECTED, 2 PART EPOXY, LOCKED INTO EXTRUDED CHANNELS
3. **BASE FINISH:** MILL
4. **POURED CONCRETE STAIRS:** NOSING SHALL TERMINATE NO MORE THEN 3" FROM END OF STEPS
5. **CONCRETE FILLED STEEL PAN STAIRS:** NOSING SHALL BE FULL LENGTH OF STEPS, LESS 1/8" CLEARANCE
6. **COLOR:** BLACK (STANDARD), SAFETY YELLOW, GRAY, RED, BROWN, GREEN, BURGUNDY, BLUE, BUFF, LUMINESCENT

7. **LENGTH:** 120" MAXIMUM
8. HOLES ARE DRILLED FOR A MIN. 3/16" x 1-1/4" CONCRETE FASTENER SPACED 3" FROM ENDS AND APPROXIMATELY 12" TO 15" O.C.
9. UL 1994 LISTED: COMBINED WIDTH OF PHOTO-LUMINESCENT MATERIAL SHALL NOT BE LESS THAN 1"

LENGTH	QTY	COLOR

PROJECT:					
ARCHITECT:					
CONTRACTOR:					
QTY:					
PART#:		STRB-A11D			
 9300 73rd Avenue North Minneapolis, MN 55428		TITLE:			
		V505S, Stair Tread, Bar Ribbed Abrasive, Long Nose Angled, Drilled For Bolt In,			
	NAME	DATE	SIZE	DWG. NO.	REV
DRAWN	BMH	3/11/11	A	Nystrom STN STRB-A11D ShpDr	A
RELEASED	PE	3/11/11	WEIGHT: 4.7 LB		SHEET 1 OF 1

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF NYSTROM. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF NYSTROM IS PROHIBITED.