

MODEL A5D

(RENOVATION RIBBED ABRASIVE BARS)

Distributed by:

Canadian Master Distributor

✉ sales@cityscapesupply.com

🌐 cityscapesupply.com

☎ 647 498 3417



SPECIFICATIONS:

① **BASE:** EXTRUDED ALUMINUM ALLOY 6063 T-5

② **ABRASIVE:** ALUMINUM OXIDE SILICON CARBIDE
GRANULES IN A UV PROTECTED, 2 PART EPOXY,
LOCKED INTO EXTRUDED CHANNELS

3. **BASE FINISH:** MILL


4. **POURED CONCRETE STAIRS:** NOSING SHALL
TERMINATE NO MORE THEN 3" FROM END OF STEPS

5. **CONCRETE FILLED STEEL PAN STAIRS:** NOSING
SHALL BE FULL LENGTH OF STEPS, LESS 1/8"
CLEARANCE

6. **COLOR:** BLACK (STANDARD), SAFETY YELLOW,
GRAY, RED, BROWN, GREEN, BURGUNDY, BLUE,
BUFF, LUMINESCENT

7. **LENGTH:** 12'0" MAXIMUM
8. HOLES ARE DRILLED FOR A MIN. 3/16" x 1-1/4" CONCRETE
FASTENER SPACED 3" FROM ENDS AND
APPROXIMATELY 12" TO 15" O.C.
9. UL 1994 LISTED: COMBINED WIDTH OF PHOTO-
LUMINESCENT MATERIAL SHALL NOT BE LESS
THAN 1"

LENGTH	QTY	COLOR

PROJECT:			
ARCHITECT:			
CONTRACTOR:			
QTY:			
PART#:		STRB-A5D	
 9300 73rd Avenue North Minneapolis, MN 55428		TITLE:	
		V470S, Stair Tread, Bar Ribbed Abrasive, Long Nose Angled, Drilled For Bolt In,	
NAME	DATE	SIZE	DWG. NO.
DRAWN	DKL	6/3/16	A
RELEASED	DT	6/3/16	WEIGHT: 2 LB
Nystrom STN STRB-A5D ShpDr			REV A
SHEET 1 OF 1			