

Distributed by:

Canadian Master Distributor

✉ sales@cityscapesupply.com

🌐 cityscapesupply.com

☎ 647 498 3417



SPECIFICATIONS:

① **BASE:** EXTRUDED ALUMINUM ALLOY 6063 T-5

② **ABRASIVE:** ALUMINUM OXIDE SILICON CARBIDE GRANULES IN A UV PROTECTED, 2 PART EPOXY, LOCKED INTO EXTRUDED CHANNELS

3. **BASE FINISH:** MILL


4. **POURED CONCRETE STAIRS:** NOSING SHALL TERMINATE NO MORE THEN 3" FROM END OF STEPS

5. **CONCRETE FILLED STEEL PAN STAIRS:** NOSING SHALL BE FULL LENGTH OF STEPS, LESS 1/8" CLEARANCE

6. **COLOR:** BLACK (STANDARD), SAFETY YELLOW, GRAY, RED, BROWN, GREEN, BURGUNDY, BLUE, BUFF, LUMINESCENT

7. **LENGTH:** 12'0" MAXIMUM
8. **HOLES ARE DRILLED FOR A MIN. 3/16" x 1-1/4" CONCRETE FASTENER SPACED 3" FROM ENDS AND APPROXIMATELY 12" TO 15" O.C.**
9. **UL 1994 LISTED:** COMBINED WIDTH OF PHOTO-LUMINESCENT MATERIAL SHALL NOT BE LESS THAN 1"

LENGTH	QTY	COLOR

PROJECT:					
ARCHITECT:					
CONTRACTOR:					
QTY:					
PART#:				STRB-A9D	
 9300 73rd Avenue North Minneapolis, MN 55428				TITLE:	
				V500S, Stair Tread, Bar Ribbed Abrasive, Long Nose Angled, Drilled For Bolt In,	
	NAME	DATE	SIZE	DWG. NO.	REV
DRAWN	BMH	3/11/11	A	Nystrom STN STRB-A9D ShpDr	A
RELEASED	PE	3/11/11	WEIGHT: 3.75 LB	SHEET 1 OF 1	