

(RENOVATION RIBBED ABRASIVE BARS)

SPECIFICATIONS:

- (1) BASE: EXTRUDED ALUMINUM ALLOY 6063 T-5
- $\langle 2 \rangle$ **ABRASIVE**: ALUMINUM OXIDE SILICON CARBIDE GRANULES IN A UV PROTECTED, 2 PART EPOXY, LOCKED INTO EXTRUDED CHANNELS
- 3. BASE FINISH: MILL
- 4. POURED CONCRETE STAIRS: NOSING SHALL TERMINATE NO MORE THEN 3" FROM END OF
- 5. CONCRETE FILLED STEEL PAN STAIRS: NOSING SHALL BE FULL LENGTH OF STEPS, LESS 1/8" **CLEARANCE**
- 6. COLOR: BLACK (STANDARD), SAFETY YELLOW, GRAY, RED, BROWN, GREEN, BURGUNDY, BLUE, BUFF, LUMINESCENT

- 7. LENGTH: 12'0" MAXIMUM
- 8. HOLES ARE DRILLED FOR A MIN. 3/16" x 1-1/4" CONCRETE FASTENER SPACED 3" FROM ENDS AND APPROXIMATELY 12" TO 15" O.C.
- 9. UL 1994 LISTED: COMBINED WIDTH OF PHOTO-LUMINESCENT MATERIAL SHALL NOT BE LESS THAN 1"

LENGTH	QTY	COLOR

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF NYSTROM. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF NYSTROM IS PROHIBITED.

Canadian Master Distributor

sales@cityscapesupply.com

cityscapesupply.com

647 498 3417

PROJECT: ARCHITECT: CONTRACTOR: QTY: PART#: STRB-L5D TITLE: V470, Stair Tread, nystrom Bar Ribbed Abrasive, Long Nose, Drilled For Bolt In, 9300 73rd Avenue North Minneapolis, MN 55428 NAME DATE SIZE DWG. NO. REV Nystrom STN STRB-L5D ShpDr Α Α DRAWN **BMH** 3/11/11 RELEASED PE WEIGHT: 2 LB SHEET 1 OF 1 3/11/11

CITYSCAPESUPPLY