

# MODEL V4D

(RENOVATION RIBBED ABRASIVE BARS)

## Distributed by:

**CITYSCAPESUPPLY** 

PROJECT:

ARCHITECT:

## **Canadian Master Distributor**

sales@cityscapesupply.com

REV

Α

cityscapesupply.com

647 498 3417

#### SPECIFICATIONS:

В

- (1) BASE: EXTRUDED ALUMINUM ALLOY 6063-T5
- ② ABRASIVE: ALUMINUM OXIDE SILICON CARBIDE GRANDULES IN A UV PROTECTED, 2 PART, EPOXY, LOCKED INTO EXTRUDED CHANNELS
- **BASE FINISH: MILL**
- POURED CONCRETE STAIRS: NOSING SHALL TERMINATE NO MORE THAN 3" FROM END OF STEPS
- **CONCRETE FILLED STEEL PAN STAIRS: NOSING SHALL** BE FULL LENGTH OF STEPS, LESS 1/8" CLEARANCE
- 6. COLOR: BLACK (STANDARD), SAFETY YELLOW, GRAY, RED, BROWN, GREEN, BURGUNDY, BLUE AND BUFF, LUMINESCENT

#### 7. LENGTH: 12'0" MAXIMUM

- 8. HOLES ARE DRILLED FOR A MIN. 3/16" x 1-1/4" CONCRETE FASTENER SPACED 3" FROM ENDS AND APPROXIMATELY 12" TO 15" O.C.
- 9. UL 1994 LISTED: COMBINED WIDTH OF PHOTO-LUMINESCENT MATERIAL SHALL NOT BE LESS THAN 1"

LENGTH	QTY	COLOR

CONTRACTOR: QTY: PART#: STRB-V4D TITLE: N-RB40, Stair Tread, Bar Ribbed Abrasive, V-Nose, Drilled For Bolt In, 9300 73rd Avenue North Minneapolis, MN 55428 NAME DATE SIZE DWG. NO. Nystrom STN STRB-V4D ShpDr Α DRAWN 12/14/11 RELEASED PE WEIGHT: VARIES SHEET 1 OF 1 12/14/11

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF NYSTROM. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF NYSTROM IS PROHIBITED.