

(SINGLE STAGE RIBBED ABRASIVE BARS)

## SPECIFICATIONS:

- $\langle 1 \rangle$  **BASE**: EXTRUDED ALUMINUM ALLOY 6063 T-5
- $\langle 2 \rangle$  **ABRASIVE**: ALUMINUM OXIDE SILICON CARBIDE GRANULES IN A UV PROTECTED, 2 PART EPOXY, LOCKED INTO EXTRUDED CHANNELS
- 3. BASE FINISH: MILL
- 4. POURED CONCRETE STAIRS: NOSING SHALL TERMINATE NO MORE THEN 3" FROM END OF STEPS
- 5. CONCRETE FILLED STEEL PAN STAIRS: NOSING SHALL BE FULL LENGTH OF STEPS, LESS 1/8" **CLEARANCE**
- 6. COLOR: BLACK (STANDARD), SAFETY YELLOW, GRAY, RED, BRÒWN, GREEN, BURGUNDY, BLUE, BUFF, LUMINESCENT
- 7. LENGTH: 12'0" MAXIMUM 8. UL 1994 LISTED: COMBINED WIDTH OF PHOTO-LUMINESCENT MATERIAL SHALL NOT BE LESS THAN 1"

LENGTH	QTY	COLOR
	LENGTH	LENGTH QTY

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF NYSTROM. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF NYSTROM IS PROHIBITED.

## Distributed by:

## **Canadian Master Distributor**

sales@cityscapesupply.com

cityscapesupply.com

**CITYSCAPESUPPLY** 647 498 3417

PROJECT:							
ARCHITECT:							
CONTRACTOR:							
QTY:							
PART#:			STSB-A3E				
<b>▶ </b> ¶ nystrom <sup>®</sup>			TITLE: V851, Stair Tread, Bar Ribbed Abrasive,				
9300 73rd Avenue North Minneapolis, MN 55428			Long Nose Angled, Alum Extruded Anchor,				
	NAME	DATE	SIZE	DWG. NO.			REV
DRAWN	ВМН	3/11/11	Α	Nystrom STI	N STSB-A3E S	ShpDr	Α
RELEASED	PE	3/11/11	WE	IGHT: 1.33 LB		SHEET 1 (	OF 1