

MODEL L1.875E

(SINGLE STAGE RIBBED ABRASIVE BARS)

SPECIFICATIONS:

- ① **BASE:** EXTRUDED ALUMINUM ALLOY 6063 T-5
- ② **ABRASIVE:** ALUMINUM OXIDE SILICON CARBIDE GRANULES IN A UV PROTECTED, 2 PART EPOXY, LOCKED INTO EXTRUDED CHANNELS
3. **BASE FINISH:** MILL
4. **POURED CONCRETE STAIRS:** NOSING SHALL TERMINATE NO MORE THEN 3" FROM END OF STEPS
5. **CONCRETE FILLED STEEL PAN STAIRS:** NOSING SHALL BE FULL LENGTH OF STEPS, LESS 1/8" CLEARANCE

6. **COLOR:** BLACK (STANDARD), SAFETY YELLOW, GRAY, RED, BROWN, GREEN, BURGUNDY, BLUE, BUFF, LUMINESCENT
7. **LENGTH:** 12'0" MAXIMUM
8. **UL 1994 LISTED:** COMBINED WIDTH OF PHOTO-LUMINESCENT MATERIAL SHALL NOT BE LESS THAN 1"

LENGTH	QTY	COLOR

Distributed by:


Canadian Master Distributor

✉ sales@cityscapesupply.com

🌐 cityscapesupply.com

☎ 647 498 3417



PROJECT:				
ARCHITECT:				
CONTRACTOR:				
QTY:				
PART#:		STSB-L1.875E		
 9300 73rd Avenue North Minneapolis, MN 55428		TITLE:		
		V431, Stair Tread, Bar Ribbed Abrasive, Long Nose, Alum Extruded Anchor		
NAME	DATE	SIZE	DWG. NO.	REV
DRAWN BMH	3/11/11	A	Nystrom STN STSB-L1.875E ShpDr	A
RELEASED PE	3/11/11	WEIGHT: .90 LB	SHEET 1 OF 1	