

MODEL P3E

(SINGLE STAGE RIBBED ABRASIVE BARS)

SPECIFICATIONS:

- (1) **BASE**: EXTRUDED ALUMINUM ALLOY 6063 T-6
- (2) ABRASIVE: ALUMINUM OXIDE SILICON CARBIDE GRANULES IN A UV PROTECTED, 2 PART EPOXY, LOCKED INTO EXTRUDED CHANNELS
- 3. BASE FINISH: MILL
- 4. POURED CONCRETE STAIRS: NOSING SHALL TERMINATE NO MORE THEN 3" FROM END OF STEPS
- 5. CONCRETE FILLED STEEL PAN STAIRS: NOSING SHALL BE FULL LENGTH OF STEPS, LESS 1/8" CLEARANCE
- 6. **COLOR:** BLACK (STANDARD), SAFETY YELLOW, GRAY, RED, BROWN, GREEN, BURGUNDY, BLUE, BUFF, LUMINESCENT
- 7. **LENGTH:** 12'0" MAXIMUM
- 8. UL 1994 LISTED: COMBINED WIDTH OF PHOTO-LUMINESCENT MATERIAL SHALL NOT BE LESS THAN 1"

LENGTH	QTY	COLOR

Distributed by:

Canadian Master Distributor

 \bowtie sales@cityscapesupply.com

cityscapesupply.com

647 498 3417

	PROJECT:						
ARCHITECT: CONTRACTOR:							
	QTY:						
	PART#:				STSB-P3E		
	▶ (nystrom				TITLE: V951, Stair Tread, Bar Ribbed Abrasive, Short Nose, Alum Extruded Anchor,		
9300 73rd Avenue North Minneapolis, MN 55428							
		NAME	DATE	SIZE	DWG. NO.		REV
	DRAWN	ВМН	3/11/11	Α	Nystrom STN STSB-P3E ShpDr		Α
	RELEASED	PE	3/11/11	WE	IGHT: 1.17 LB	SHEET 1 (OF 1

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF NYSTROM. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF NYSTROM IS PROHIBITED.

1