

(SINGLE STAGE RIBBED ABRASIVE BARS)

SPECIFICATIONS:

- $\langle 1 \rangle$ **Base**: Extruded Aluminum Alloy 6063 T-5
- (2) ABRASIVE: ALUMINUM OXIDE SILICON CARBIDE GRANULES IN A UV PROTECTED, 2 PART EPOXY, LOCKED INTO EXTRUDED CHANNELS
- 3. BASE FINISH: MILL
- 4. **POURED CONCRETE STAIRS:** NOSING SHALL TERMINATE NO MORE THEN 3" FROM END OF STEPS
- 5. CONCRETE FILLED STEEL PAN STAIRS: NOSING SHALL BE FULL LENGTH OF STEPS, LESS 1/8" CLEARANCE
- COLOR: BLACK (STANDARD), SAFETY YELLOW, GRAY, RED, BROWN, GREEN, BURGUNDY, BLUE, BUFF, LUMINESCENT
- 7. LENGTH: 12'0" MAXIMUM
- 8. UL 1994 LISTED: COMBINED WIDTH OF PHOTO-LUMINESCENT MATERIAL SHALL NOT BE LESS THAN 1"

LENGTH	QTY	COLOR
·		

Distributed by:

CITYSCAPESUPPLY

Canadian Master Distributor

🖂 sales@cityscapesupply.com

cityscapesupply.com

PROJECT: ARCHITECT: CONTRACTOR: QTY: PART#: STSB-P4E TITLE: V971, Stair Tread, Bar Ribbed Abrasive, Short Nose, Alum Extruded Anchor 9300 73rd Avenue North Minneapolis, MN 55428 NAME DATE SIZE DWG. NO. REV Nystrom STN STSB-P4E ShpDr Α Α DRAWN **BMH** 3/11/11 RELEASED PE WEIGHT: 1.50 LB SHEET 1 OF 1 3/11/11

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF NYSTROM. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF NYSTROM IS PROHIBITED.

- 1