

## MODEL STSF-C4D

(SINGLE STAGE FULL ABRASIVE)

## SPECIFICATIONS:

- 1 BASE: EXTRUDED ALUMINUM ALLOY 6063 T-5
- (2) ABRASIVE: ALUMINUM OXIDE SILICON CARBIDE GRANULES IN A UV PROTECTED, 2 PART EPOXY, LOCKED INTO EXTRUDED CHANNELS
- 3. BASE FINISH: MILL
- 4. POURED CONCRETE STAIRS: NOSING SHALL TERMINATE NO MORE THEN 3" FROM END OF STEPS
- 5. CONCRETE FILLED STEEL PAN STAIRS: NOSING SHALL BE FULL LENGTH OF STEPS, LESS 1/8" CLEARANCE
- 6. COLOR: BLACK (STANDARD), SAFETY YELLOW, GRAY, RED, BROWN, GREEN, BURGUNDY, BLUE, BUFF, LUMINESCENT

- 7. **LENGTH:** 12'0" MAXIMUM
- 8. COUNTER SUNK HOLES PRE-DRILLED FOR A #10 FASTENER SPACED 3" FROM ENDS AND APPROXIMATELY 12" TO 15" O.C.
- APPROXIMATELY 12" TO 15" O.C.

  9. UL 1994 LISTED: COMBINED WIDTH OF PHOTO-LUMINESCENT MATERIAL SHALL NOT BE LESS THAN 1"

LENGTH	QTY	COLOR		

Distributed by:

## **Canadian Master Distributor**

 $\bowtie$  sales@cityscapesupply.com

cityscapesupply.com

		PROJEC	)):					
	ARCHITECT:							
CONTRACTOR: QTY:								
	PART#:				STSF-C4D			
9300 73rd Avenue North Minneapolis, MN 55428					TITLE: Stair Tread, Full Abrasive, Short Nose, Alum, Drilled Single Stage			
		NAME	DATE	SIZE	DWG. NO.			REV
	DRAWN	DKL	6/14/17	Α		STSF-C4D		Α
	RELEASED	DT	6/14/17	WE	IGHT: 1.50 LB		SHEET 1 (	OF 1

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF NYSTROM. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF NYSTROM IS PROHIBITED.

1