MODEL STSF-C4E

(SINGLE STAGE FULL ABRASIVE)

SPECIFICATIONS:

- (1) BASE: EXTRUDED ALUMINUM ALLOY 6063 T-5
- (2) ABRASIVE: ALUMINUM OXIDE SILICON CARBIDE GRANULES IN A UV PROTECTED, 2 PART EPOXY, LOCKED INTO EXTRUDED CHANNELS
- 3. BASE FINISH: MILL
- 4. POURED CONCRETE STAIRS: NOSING SHALL TERMINATE NO MORE THEN 3" FROM END OF STEPS
- 5. CONCRETE FILLED STEEL PAN STAIRS: NOSING SHALL BE FULL LENGTH OF STEPS, LESS 1/8" CLEARANCE
- 6. COLOR: BLACK (STANDARD), SAFETY YELLOW, GRAY, RED, BROWN, GREEN, BURGUNDY, BLUE, BUFF, LUMINESCENT

- 7. **LENGTH:** 12'0" MAXIMUM
- 8. **UL 1994 LISTED:** COMBINED WIDTH OF PHOTO-LUMINESCENT MATERIAL SHALL NOT BE LESS THAN 1"

QTY	COLOR
	QTY

Distributed by:

CITYSCAPESUPPLY

Canadian Master Distributor

 \bowtie sales@cityscapesupply.com

cityscapesupply.com

647 498 3417

		PROJEC	CT:					
	Α	RCHITE	CT:					
CONTRACTOR: QTY:								
	PART#:				STSF-C4E			
9300 73rd Avenue North Minneapolis, MN 55428				n	TITLE:	Stair Tread, Full Abrasive, Short Nose, Alum Extrud Single Stage	ed Anchor,	
		NAME	DATE	SIZE	DWG. N	-		REV
	DRAWN	DKL	4/17/17	Α		STSF-C4E		A
	DELEVOED	DT	4/47/47	\A/E	ICLIT: 4 F	N I D	CLIEFT 4	OF 4

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF NYSTROM. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF NYSTROM IS PROHIBITED.