2 4" 3½"

## MODEL STSF-L4D

(SINGLE STAGE FULL ABRASIVE)

## SPECIFICATIONS:

- 1 BASE: EXTRUDED ALUMINUM ALLOY 6063 T-5
- (2) ABRASIVE: ALUMINUM OXIDE SILICON CARBIDE GRANULES IN A UV PROTECTED, 2 PART EPOXY, LOCKED INTO EXTRUDED CHANNELS
- 3. BASE FINISH: MILL
- 4. POURED CONCRETE STAIRS: NOSING SHALL TERMINATE NO MORE THEN 3" FROM END OF STEPS
- 5. CONCRETE FILLED STEEL PAN STAIRS: NOSING SHALL BE FULL LENGTH OF STEPS, LESS 1/8" CLEARANCE
- 6. COLOR: BLACK (STANDARD), SAFETY YELLOW, GRAY, RED, BROWN, GREEN, BURGUNDY, BLUE, BUFF, LUMINESCENT

- 7. **LENGTH:** 12'0" MAXIMUM
- 8. COUNTER SUNK HOLES PRE-DRILLED FOR A #10 FASTENER SPACED 3" FROM ENDS AND APPROXIMATELY 12" TO 15" O.C.
- APPROXIMATELY 12" TO 15" O.C.

  9. UL 1994 LISTED: COMBINED WIDTH OF PHOTO-LUMINESCENT MATERIAL SHALL NOT BE LESS THAN 1"

LENGTH	QTY	COLOR

Distributed by:

## **Canadian Master Distributor**

cityscapesupply.com

	PROJEC	CT:					
Α	RCHITE	CT:					
co	NTRAC	TOR:					
	QTY:						
	PART#	<b>#</b> :					
9300 73rd Avenue North Minneapolis, MN 55428			TITLE: Stair Tread, Full Abrasive, Long Nose, Alum, Drilled Single Stage				
	NAME	DATE	SIZE	DWG. NO.			REV
DRAWN	DKL	6/14/17	Α		STSF-L4D		Α .
RELEASED	DT	6/14/17	WE	IGHT: 1.50 LB	-	SHEET 1	OF 1

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF NYSTROM. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF NYSTROM IS PROHIBITED.

1