

## MODEL N0.75D

(ARCHITECTURAL INSET)

### SPECIFICATIONS:

- ① **BASE:** EXTRUDED ALUMINUM ALLOY 6063 T-5
- ② **ABRASIVE:** ALUMINUM OXIDE SILICON CARBIDE GRANULES IN A UV PROTECTED, 2 PART EPOXY, LOCKED INTO EXTRUDED CHANNELS
3. **BASE FINISH:** MILL
4. **POURED CONCRETE STAIRS:** NOSING SHALL TERMINATE NO MORE THEN 3" FROM END OF STEPS
5. **CONCRETE FILLED STEEL PAN STAIRS:** NOSING SHALL BE FULL LENGTH OF STEPS, LESS 1/8" CLEARANCE
6. COUNTERSUNK HOLES PRE-DRILLED FOR A #10 FASTENER SPACED 3" FROM ENDS AND APPROXIMATELY 12" - 15" O.C.

7. **COLOR:** BLACK (STANDARD), SAFETY YELLOW, GRAY, RED, BROWN, GREEN, BURGUNDY, BLUE, BUFF, LUMINESCENT
8. **LENGTH:** 12'0" MAXIMUM
9. UL 1994 LISTED: COMBINED WIDTH OF PHOTO-LUMINESCENT MATERIAL SHALL NOT BE LESS THAN 1"

LENGTH	QTY	COLOR

Distributed by:




**Canadian Master Distributor**

✉ sales@cityscapesupply.com

🌐 cityscapesupply.com

☎ 647 498 3417

PROJECT:					
ARCHITECT:					
CONTRACTOR:					
QTY:					
PART#:			STSB-N0.75D		
 9300 73rd Avenue North Minneapolis, MN 55428			TITLE:		
			V1GG Stair Tread, CE&C : 44 No Nose, Drilled Anchor Holes		
	NAME	DATE	SIZE	DWG. NO.	REV
DRAWN	DKL	11/26/13	A	Nystrom STN STSB-N0.75D ShpDr	B
RELEASED	PE	11/26/13	WEIGHT: .35 LB		SHEET 1 OF 1