



MODEL NO.75E

(SINGLE STAGE RIBBED ABRASIVE BAR)

SPECIFICATIONS:

- (1) **BASE**: HEAT TREATED EXTRUDED ALUMINUM ALLOY 6063 T-5
- (2) ABRASIVE: ALUMINUM OXIDE SILICON CARBIDE GRANULES IN A UV PROTECTED, 2 PART EPOXY, LOCKED INTO EXTRUDED CHANNELS
- 3. BASE FINISH: MILL
- 4. **POURED CONCRETE STAIRS:** NOSING SHALL TERMINATE NO MORE THEN 3" FROM END OF STEPS
- 5. CONCRETE FILLED STEEL PAN STAIRS: NOSING SHALL BE FULL LENGTH OF STEPS, LESS 1/8" CLEARANCE

- COLOR: BLACK (STANDARD), SAFETY YELLOW, GRAY, RED, BROWN, GREEN, BURGUNDY, BLUE, BUFF, LUMINESCENT
- 7. LENGTH: 12'0" MAXIMUM
- 3. UL 1994 LISTED: COMBINED WIDTH OF PHOTO-LUMINESCENT MATERIAL SHALL NOT BE LESS THAN 1"

QTY	COLOR
	QTY

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF NYSTROM. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF NYSTROM IS PROHIBITED.

Distributed by:

CITYSCAPSUPPLY

Canadian Master Distributor

⊠ sales@cityscapesupply.com

cityscapesupply.com

647 498 3417

I	PROJEC	CT:					
A	RCHITE	CT:					
CO	NTRAC	TOR:					
	QTY:						
PART#:			STSB-N0.75E				
Right to site. 9300 73rd Avenue North Brooklyn Park, MN 55428			TITLE:	V111, Stair Tread, Bar Ribbed Abrasive Nose, Alum Extruded) ,		
	NAME	DATE	SIZE	DWG. NO.			REV
DRAWN	DKL	11/26/13	Α		STSB-N0.75E		В
DELEVOED	DE	11/26/12	١٨/٥	ICUT: 25 I D		CHEET 4 (75.4

1