

MODEL STSF-P4E

(SINGLE STAGE FULL ABRASIVE)

SPECIFICATIONS:

- 1 BASE: EXTRUDED ALUMINUM ALLOY 6063 T-5
- (2) ABRASIVE: ALUMINUM OXIDE SILICON CARBIDE GRANULES IN A UV PROTECTED, 2 PART EPOXY, LOCKED INTO EXTRUDED CHANNELS
- 3. BASE FINISH: MILL
- 4. POURED CONCRETE STAIRS: NOSING SHALL TERMINATE NO MORE THEN 3" FROM END OF STEPS
- 5. CONCRETE FILLED STEEL PAN STAIRS: NOSING SHALL BE FULL LENGTH OF STEPS, LESS 1/8" CLEARANCE
- 6. COLOR: BLACK (STANDARD), SAFETY YELLOW, GRAY, RED, BROWN, GREEN, BURGUNDY, BLUE, BUFF, LUMINESCENT

- 7. **LENGTH:** 12'0" MAXIMUM
- 8. **UL 1994 LISTED:** COMBINED WIDTH OF PHOTO-LUMINESCENT MATERIAL SHALL NOT BE LESS THAN 1"

QTY	COLOR
	QTY

Distributed by:

Canadian Master Distributor

cityscapesupply.com

647 498 3417

	PROJECT:						
	ARCHITECT:						
	CONTRACTOR: QTY:						
	PART#:				STSF-P4E		
9300 73rd Avenue North Minneapolis, MN 55428					TITLE: Stair Tread, Full Abrasive, Short Nose, Alum Extruded Anchor, Single Stage		
		NAME	DATE	SIZE	DWG. NO.		REV
	DRAWN	DKL	4/17/17	Α	STSF-P4E		Α
	RELEASED	DT	4/17/17	WE	IGHT: 1.50 LB	SHEET 1 (OF 1

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF NYSTROM. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF NYSTROM IS PROHIBITED.

1