

MODEL P3.375E

(TWO STAGE RIBBED ABRASIVE BARS)

SPECIFICATIONS:

- ① **BASE:** EXTRUDED ALUMINUM ALLOY 6063 T-6
- ② **ABRASIVE:** ALUMINUM OXIDE SILICON CARBIDE GRANULES IN A UV PROTECTED, 2 PART EPOXY, LOCKED INTO EXTRUDED CHANNELS
3. **BASE FINISH:** MILL
4. **POURED CONCRETE STAIRS:** NOSING SHALL TERMINATE NO MORE THEN 3" FROM END OF STEPS
5. **CONCRETE FILLED STEEL PAN STAIRS:** NOSING SHALL BE FULL LENGTH OF STEPS, LESS 1/8" CLEARANCE

6. **COLOR:** BLACK (STANDARD), SAFETY YELLOW, GRAY, RED, BROWN, GREEN, BURGUNDY, BLUE, BUFF, LUMINESCENT
7. **LENGTH:** 12'0" MAXIMUM
8. **UL 1994 LISTED:** COMBINED WIDTH OF PHOTO-LUMINESCENT MATERIAL SHALL NOT BE LESS THAN 1"

LENGTH	QTY	COLOR

Distributed by:




Canadian Master Distributor

✉ sales@cityscapesupply.com

🌐 cityscapesupply.com

☎ 647 498 3417

PROJECT:				
ARCHITECT:				
CONTRACTOR:				
QTY:				
PART#:		STTB-P3.375E		
 9300 73rd Avenue North Minneapolis, MN 55428		TITLE: Two Stage Rib, Stair Tread, Bar Ribbed Abrasive, Short Nose, Alum Extruded Anchor,		
NAME	DATE	SIZE	DWG. NO.	REV
DRAWN DKL	11/2/16	A	Nystrom STN STTB-P3.375E ShpDr	A
RELEASED DT	11/2/16	WEIGHT: 2 LB	SHEET 1 OF 1	